



KDAU-4141-000 - 16 X 230VAC/4A MODULE



DESCRIPTION

16x AC/DC Outputs module with up to 230VAC/4A switching capacity and L, N, PE terminals for 4 of 5 outputs.

TECHNICAL INFORMATION

- 16 x 230VAC/4A Relais output module
- Total current, max 13A
- Wago cage clamp terminals
- 13 Outputs with L/N/PE terminals
- 3 Output with L terminal
- Fuse protection
- For connexion to any KDIO channel

ELECTRICAL

KDIO BUS

- Address [0..7]
- 2 RJ45 Connectors for up to 8 modules in cascade connections

SWITCHING CAPACITY

- 4A @ 250VAC
- 8A @ 125VAC
- 1A @ 30 VDC

KDAU-4141-000 - 16 X 230VAC/4A MODULE

SUPPLY

- 230VAC 13A
- 13A F Fuse protection

CONNEXIONS

- 2 x KDIO channel connectors
- 1 x 24VDC relay supply WAGO 2 pins 733-332 for cable connector WAGO 733-102



- Power with L, N, PE cage clamps terminals
- 13 x output with L, N, PE cage clamps terminals
- 3 x output with L cage clamps terminal

MECHANICAL

DIMENSIONS

- L 160.0mm x H 90mm x 58mm
- Conform for 35mm DIN Rail mount (DIN 43880) or direct surface mount
- IP30 protection