



# KDAU-5000 - 16 x INPUTS 24VDC Module

---



## DESCRIPTION

---

- 16 PNP inputs 24VDC module
- All inputs fitted with
  - ◆ WAGO 3 pins 733-333 connectors for direct sensor connexion
    - ◇ with 0V, +24V and input signal
    - ◇ Compatible cable connector WAGO 733-103
- Supply connector
  - ◆ WAGO 2 pins 733-332
    - ◇ Compatible cable connector WAGO 733-102
- KDIO Bus address selectable from 0 to 7

## TECHNICAL INFORMATION

---

### ELECTRICAL

---

### KDIO BUS

---

- Address [0..7] selectable
- 2 x KDIO flat cable interconnection connector for up to 8 modules in cascade connections

### INPUT LEVELS & CURRENTS

---

- 0 < 3.5 V
- 1 > 9.5 V
- Current 1.6 mA @ 24V
- Absolute maximum voltage at any inputs: 260V

### CONNECTION


---

### SUPPLY

---

- WAGO 2 pins 733-332 for cable connector WAGO 733-102


## KDAU-5000 - 16 x INPUTS 24VDC Module



### INPUTS

---

- WAGO 3 pins 733-333 for cable connector WAGO 733-103



### MECHANICAL

---

- Dimensions: L 67.5 X H 92.6
- Conform for rail mount for norms DIN EN 50022, DIN EN 50035 & DIN EN 50045

[www.cdisa.ch](http://www.cdisa.ch)

Rev 20 - 09 Jan 2009 - 18:09:18