



KDAU-5000 - 16 x INPUTS 24VDC Module



DESCRIPTION

- 16 PNP inputs 24VDC module
- All inputs fitted with
 - ◆ WAGO 3 pins 733-333 connectors for direct sensor connexion
 - ◆ with 0V, +24V and input signal
 - ◆ Compatible cable connector WAGO 733-103
- Supply connector
 - ◆ WAGO 2 pins 733-332
 - ◆ Compatible cable connector WAGO 733-102
- KDIO Bus address selectable from 0 to 7

TECHNICAL INFORMATION

ELECTRICAL

KDIO BUS

- Address [0..7] selectable
- 2 x KDIO flat cable interconnection connector for up to 8 modules in cascade connections

INPUT LEVELS & CURRENTS


- 0 < 3.5 V
- 1 > 9.5 V
- Current 1.6 mA @ 24V
- Absolute maximum voltage at any inputs: 260V

CONNECTION

SUPPLY


- WAGO 2 pins 733-332 for cable connector WAGO 733-102

KDAU-5000 - 16 x INPUTS 24VDC Module



INPUTS

- WAGO 3 pins 733-333 for cable connector WAGO 733-103



MECHANICAL

- Dimensions: L 67.5 X H 92.6
- Conform for rail mount for norms DIN EN 50022, DIN EN 50035 & DIN EN 50045

www.cdisa.ch

Rev 20 - 09 Jan 2009 - 18:09:18