

# KDAU-5201 - 8 x INPUTS PNP 24VDC + 8 x OUTPUTS PNP 24VDC/0.5A MODULE

---



## DESCRIPTION

---

### INPUTS

---

- 8 PNP inputs 24VDC
- All inputs fitted with
  - ◆ WAGO 3 pins 733-333 connectors for direct sensor connexion
    - ◇ with 0V, +24V and input signal
    - ◇ Compatible cable connector WAGO 733-103

### OUTPUTS

---

- 8 NPN outputs 24VDC/0.5A module
- All outputs fitted with
  - ◆ WAGO 2 pins 733-332 connectors for direct load connexion
    - ◇ with NPN output, and +24V
    - ◇ Compatible cable connector WAGO 733-102

## TECHNICAL INFORMATION

---

### ELECTRICAL

---

#### KDIO BUS

---

- Address [0..7] selectable
- 2 x KDIO flat cable interconnection connector for up to 8 modules in cascade connections

### INPUTS

---

- Levels
  - ◆ 0 < 3.5 V
  - ◆ 1 > 9.5 V

## KDAU-5201 - 8 x INPUTS PNP 24VDC + 8 x OUTPUTS PNP 24VDC/0.5A MODULE

- Current 1.6 mA @ 24V
- Absolute maximum voltage at any inputs: 260V

### OUTPUTS

---

- Maximal current 0.5A per output
- Total simultaneous output current for all outputs 2.0A

### SUPPLY

---


- WAGO 2 pins 733-332 for cable connector WAGO 733-102



### INPUTS

---


- WAGO 3 pins 733-333 for cable connector WAGO 733-103



### OUTPUTS

---

- WAGO 2 pins 733-332 for cable connector WAGO 733-102



### MECHANICAL

---

- Dimensions: L 67.5 X H 92.6
- Conform for rail mount for norms DIN EN 50022, DIN EN 50035 & DIN EN 50045